

## **Monroe**

399 East Drive

Melbourne, FL 32904

Phone: 866.925.1664 • Fax: 321-727-7331

Email: <u>aerosales@askmonroe.com</u> Cage Code: 0WTF7

## ITEM # HL18PB5-5, HI-LOK - HL18PB5-5

Hi-Lok - Protruding Shear Head, Alloy Steel, Cadmium Plated | Diameter: 5/32", Grip Length: 5/16"





## **Specifications** | **Note**

Specifications -					
	Inventory	8253			
	Estimated Ship Date	Ships in 1 Business Day			
	Inventory Note	Need additional stock? Call (866) 925-1664 or email			
	Thread Size	8-32			
	Material	Steel Alloy			
	Head Type	Protruding Shear			
	Thread Type	8-32-UNJC-3A Modified			
	Tensile Strength	160000 to 180000 psi			
	Minimum Shear Strength	95000 psi			

Maximum Grip	5/16 in
Nominal Diameter	5/32 in
Diameter A	0.242 in 0.262 in
Reference B	0.312 in
Diameter D	0.1625 in 0.1635 in
Diameter TD	0.1570 in 0.1595 in
Reference G	0.02 in
Dimension H	0.037 in 0.047 in
Minimum Double Shear Load	4010 lb
Minimum Tension Load	1940 lb
Maximum Grip + B Tolerance	±0.010 in
Maximum Grip Tolerance	±0.005 in
Weight	.004 lb
Manufacturer	Hi-Lok
Alternate Part Number	BACB30FM5-5
Part # Unpunctuated	HL18PB55
Minimum Order Note	Minimum order is 10. Must order in increments of 10.

Note		-
Note	Our inventory is extensive. The majority of the items listed in our catalog are stocked and available for immediate shipment.	

California Residents

Prop 65 Warning: This product may contain chemicals known to the State of California to cause cancer, and birth defects or other reproductive harm.