

**Monroe**

399 East Drive

Melbourne, FL 32904

**Phone:** 855.927.2385 • **Fax:** 321-727-7331**Email:** [aerosales@askmonroe.com](mailto:aerosales@askmonroe.com) **Cage Code:** 0WTF7**ITEM # HL18PB5-5, HI-LOK - HL18PB5-5**

**Hi-Lok - Protruding Shear Head, Alloy Steel, Cadmium Plated | Diameter: 5/32", Grip Length: 5/16"**

**List Price****\$1.93****Specifications | Note****Specifications**

<b>Inventory</b>	<b>23296</b>
<b>Estimated Ship Date</b>	<b>Ships in 1 Business Day</b>
<b>Inventory Note</b>	<b>Need additional stock? Call (855) 927-2385 or <a href="#">email</a></b>
<b>Thread Size</b>	<b>8-32</b>
<b>Material</b>	<b>Steel Alloy</b>
<b>Head Type</b>	<b>Protruding Shear</b>
<b>Thread Type</b>	<b>8-32-UNJC-3A Modified</b>
<b>Tensile Strength</b>	<b>160000 to 180000 psi</b>
<b>Minimum Shear Strength</b>	<b>95000 psi</b>



<b>Maximum Grip</b>	<b>5/16 in</b>
<b>Nominal Diameter</b>	<b>5/32 in</b>
<b>Diameter A</b>	<b>0.242 in 0.262 in</b>
<b>Reference B</b>	<b>0.312 in</b>
<b>Diameter D</b>	<b>0.1625 in 0.1635 in</b>
<b>Diameter TD</b>	<b>0.1570 in 0.1595 in</b>
<b>Reference G</b>	<b>0.02 in</b>
<b>Dimension H</b>	<b>0.037 in 0.047 in</b>
<b>Minimum Double Shear Load</b>	<b>4010 lb</b>
<b>Minimum Tension Load</b>	<b>1940 lb</b>
<b>Maximum Grip + B Tolerance</b>	<b>±0.010 in</b>
<b>Maximum Grip Tolerance</b>	<b>±0.005 in</b>
<b>Weight</b>	<b>.004 lb</b>
<b>Manufacturer</b>	<b>Hi-Lok</b>
<b>Alternate Part Number</b>	<b>BACB30FM5-5</b>
<b>Part # Unpunctuated</b>	<b>HL18PB55</b>
<b>Minimum Order Note</b>	<b>Minimum order is 10. Must order in increments of 10.</b>

## Note

### Note

**Our inventory is extensive. The majority of the items listed in our catalog are stocked and available for immediate shipment.**

**California Residents**

**Prop 65 Warning: This product may contain chemicals known to the State of California to cause cancer, and birth defects or other reproductive harm.**