

**Monroe**

399 East Drive

Melbourne, FL 32904

Phone: 855.927.2385 • **Fax:** 321-727-7331**Email:** aerosales@askmonroe.com **Cage Code:** 0WTF7**ITEM # HL18PB8-5, HI-LOK - HL18PB8-5**

Hi-Lok - Protruding Shear Head, Alloy Steel, Cadmium Plated | Diameter: 1/4", Grip Length: 5/16"

List Price**\$3.39****Specifications | Note****Specifications**

| | |
|-------------------------------|----------------------------------------------------------------------------|
| Inventory | 5358 |
| Estimated Ship Date | Ships in 1 Business Day |
| Inventory Note | Need additional stock? Call (855) 927-2385 or email |
| Thread Size | 1/4-28 |
| Material | Steel Alloy |
| Head Type | Protruding Shear |
| Thread Type | 1/4-28-UNJF-3A Modified |
| Tensile Strength | 160000 to 180000 psi |
| Minimum Shear Strength | 95000 psi |



| | |
|-----------------------------------|------------------------------------------------------------|
| Maximum Grip | 5/16 in |
| Nominal Diameter | 1/4 in |
| Diameter A | 0.387 in 0.412 in |
| Reference B | 0.395 in |
| Diameter D | 0.2485 in 0.2495 in |
| Diameter TD | 0.2410 in 0.2440 in |
| Reference G | 0.03 in |
| Dimension H | 0.059 in 0.069 in |
| Minimum Double Shear Load | 9300 lb |
| Minimum Tension Load | 4300 lb |
| Maximum Grip + B Tolerance | ±0.010 in |
| Maximum Grip Tolerance | ±0.005 in |
| Weight | 0.01 lb |
| Manufacturer | Hi-Lok |
| Alternate Part Number | BACB30FM8-5 |
| NSN | 5320-00-959-0201 |
| NIIN | 00-959-0201 |
| Part # Unpunctuated | HL18PB85 |
| Minimum Order Note | Minimum order is 10. Must order in increments of 1. |

Note

Note

Our inventory is extensive. The majority of the items listed in our catalog are stocked and available for immediate shipment.

California Residents

Prop 65 Warning: This product may contain chemicals known to the State of California to cause cancer, and birth defects or other reproductive harm.