

399 East Drive Melbourne, FL 32904 Phone: 844.359.0936 • Fax: 321-727-7331 Email: <u>aerosales@askmonroe.com</u> Cage Code: 0WTF7

ITEM # HL21PB6-4, HI-LOK - HL21PB6-4

Hi-Lok - 100°, Flush Ms24694 Tension Head, Alloy Steel, Cadmium Plated | Diameter: 3/16", Grip Length: 1/4"

List Price - \$1.83



## Specifications | Note

Specifications		-
Inventory	2891	
Estimated Ship Date	Ships in 1 Business Day	
Inventory Note	Need additional stock? Call (844) 359-0936 or <u>email</u>	
Thread Size	10-32	
Material	Steel Alloy	
Head Type	Flush Tension	
Head Angle	100 °	
Thread Type	10-32-UNJF-3A Modified	
Tensile Strength	160000 to 180000 psi	
Maximum Grip	1/4 in	

Nominal Diameter	3/16 in
Diameter A	0.3765 in 0.3813 in
Diameter D	0.1885 in 0.1895 in
Diameter TD	0.1810 in 0.1840 in
Dimension H	0.0785 in 0.0805 in
Minimum Double Shear Load	5380 lb
Minimum Tension Load	3180 lb
Diameter B	0.325 in
Maximum Grip + B Tolerance	±0.010 in
Maximum Grip Tolerance	±0.005 in
Weight	.005 lb
Manufacturer	Hi-Lok
Alternate Part Number	BACB30JC6-4
NSN	5320-00-757-5503
NIIN	00-757-5503
Part # Unpunctuated	HL21PB64
Minimum Order Note	Minimum order is 10. Must order in increments of 10.

## Note

Note

Our inventory is extensive. The majority of the items listed in our catalog are stocked and available for immediate shipment.

**California Residents** 

Prop 65 Warning: This product may contain chemicals known to the State of California to cause cancer, and birth defects or other reproductive harm.