

**Monroe**

399 East Drive

Melbourne, FL 32904

**Phone:** 833.850.0782 • **Fax:** 321-727-7331**Email:** [aerosales@askmonroe.com](mailto:aerosales@askmonroe.com) **Cage Code:** 0WTF7**ITEM # HST10AG6-5, HI-LITE PIN – HST10AG6-5**

**Hi-Lite Pin – Protruding Shear Head, Titanium, Aluminum Coating | Diameter: 3/16", Grip Length: 5/16"**

**List Price**

–

**QUOTE****Specifications | Note****Specifications**

–

<b>Inventory</b>	<b>0</b>
<b>Estimated Ship Date</b>	<b>Ships within 10-14 days</b>
<b>Inventory Note</b>	<b>Need additional stock? Call (833) 850-0782 or <u><a href="#">email</a></u></b>
<b>Thread Size</b>	<b>10-32</b>
<b>Material</b>	<b>Titanium</b>
<b>Head Type</b>	<b>Protruding Shear</b>
<b>Thread Type</b>	<b>10-32-UNJF-3A Modified</b>
<b>Minimum Shear Strength</b>	<b>95000 psi</b>
<b>Maximum Grip</b>	<b>5/16 in</b>

<b>Nominal Diameter</b>	<b>3/16 in</b>
<b>Diameter A</b>	<b>0.295 in 0.315 in</b>
<b>Reference B</b>	<b>0.290 in</b>
<b>Diameter TD</b>	<b>0.1810 in 0.1840 in</b>
<b>Reference G</b>	<b>0.025 in</b>
<b>Dimension H</b>	<b>0.045 in 0.055 in</b>
<b>Minimum Double Shear Load</b>	<b>5380 lb</b>
<b>Minimum Tension Load</b>	<b>2500 lb</b>
<b>Diameter D without Lubricant</b>	<b>0.1890 in 0.1895 in</b>
<b>Diameter D with Lubricant</b>	<b>0.1885 in 0.1895 in</b>
<b>Maximum Grip + B Tolerance</b>	<b>±0.010 in</b>
<b>Maximum Grip Tolerance</b>	<b>±0.005 in</b>
<b>Weight</b>	<b>0.003 lb</b>
<b>Manufacturer</b>	<b>Hi-Lok</b>
<b>Alternate Part Number</b>	<b>BACB30VT6K5</b>
<b>Part # Unpunctuated</b>	<b>HST10AG65</b>
<b>Minimum Order Note</b>	<b>Minimum order is 10. Must order in increments of 1.</b>

## Note

### Note

**Our inventory is extensive. The majority of the items listed in our catalog are stocked and available for immediate shipment.**

**California Residents**

**Prop 65 Warning: This product may contain chemicals known to the State of California to cause cancer, and birth defects or other reproductive harm.**