

Monroe

399 East Drive

Melbourne, FL 32904

Phone: 844.223.4495 • Fax: 321-727-7331

Email: <u>aerosales@askmonroe.com</u> Cage Code: 0WTF7

ITEM # NAS1670-08L3, BLIND FASTENER - NAS1670-08L3

Blind Fastener - Grip Range: 0.157" - 0.219", Diameter: 0.164", General Purpose Blind

Fastener, Flush Head, Internally Threaded, External Sleeve

List Price - **\$4.85**

Detail	Characteristic
COUNTERSINK ANGLE	99.0 DEGREES MINIMUM AND 101.0 DEGREES MAXIMUM
EXPANSION DEVICE	SERRATED STEM-TYPE W
FASTENER LENGTH	0.278 INCHES MINIMUM AND 0.308 INCHES MAXIMUM
GRIP LENGTH	0.157 INCHES MINIMUM AND 0.219 INCHES MAXIMUM
HEAD MAJOR DIAMETER	0.325 INCHES MINIMUM AND 0.332 INCHES MAXIMUM
HEAD STYLE	FLUSH (FLAT) COUNTERSUNK (INCLUDED ANGLE - LESS THAN 135 DEG W OR W/O CHAMFER)
MATERIAL	STEEL BODY
MATERIAL	STEEL CORROSION RESISTING SLEEVE
MATERIAL	STEEL STEM
SHANK DIAMETER	0.163 INCHES MINIMUM AND 0.165 INCHES MAXIMUM
SHANK STYLE	THREADED SELF-PLUGGING SHANK W/SLEEVE
SURFACE TREATMENT	CADMIUM OVERALL





Spe	specifications -				
	Inventory	4			
	Estimated Ship Date	Ships in 1 Business Day			
	Inventory Note	Need additional stock? Call (844) 223-4495 or email			
	Features	Internally Threaded Self-Locking			
	Head Type	Flush			
	Industry Standards/Certification	NAS1670			
	Diameter	0.164 in			
	Grip Range	0.157 to 0.217 in			
	Weight	.005 lb			
	NSN	5320-00-550-2214			
	NIIN	00-550-2214			
	Part # Unpunctuated	NAS167008L3			
	Minimum Order Note	Minimum order is 5. Must order in increments of 1.			

No	te		-
	Note	Our inventory is extensive. The majority of the items listed in our catalog are stocked and available for immediate shipment.	
	California Residents	Prop 65 Warning: This product may contain chemicals known to the State of California to cause cancer, and birth defects or other reproductive harm.	